

14AF7
TO
14C5



14AF7

MEDIUM-MU TWIN TRIODE

(continued from preceding page)

Amplification Factor	17	16	16	
Plate Resistance	6500	8400	7600	ohms
Transconductance	2600	1900	2100	μ hos
Plate Current.	10.8	5	9	ma

14B6

TWIN DIODE—HIGH-MU TRIODE

Heater, for Unipotential Cathode:	
Voltage.	12.6 [□] ac or dc volts
Current.	0.15 [□] amp
<i>The 14B6 is the same as the 7B6 except for heater rating.</i>	
<input type="checkbox"/> Nominal voltage = 14.0 volts.	<input type="checkbox"/> Nominal current = 0.16 ampere.

14B8

PENTAGRID CONVERTER

Heater, for Unipotential Cathode:	
Voltage.	12.6 [□] ac or dc volts
Current.	0.15 [□] amp
<i>The 14B8 is the same as the 7B8 except for heater rating.</i>	
<input type="checkbox"/> Nominal voltage = 14.0 volts.	<input type="checkbox"/> Nominal current = 0.16 ampere.

14C5

BEAM POWER AMPLIFIER

Heater, for Unipotential Cathode:	
Voltage.	12.6 [□] ac or dc volts
Current.	0.225 [□] amp
<i>The 14C5 is the same as the 7C5 except for heater rating.</i>	
<input type="checkbox"/> Nominal voltage = 14.0 volts.	<input type="checkbox"/> Nominal current = 0.240 ampere.