

14C7

GRID-No.2 VOLTAGE. 100 max. volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:

Positive-bias value. 0 max. volts

GRID-No.2 INPUT. 0.1 max. watt

PLATE DISSIPATION. 1 max. watt

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. . . 90 max. volts
Heater positive with respect to cathode. . . 90 max. volts

▲ Nominal voltage = 14 volts.

● Nominal current = 0.16 ampere.

* With external shield JEDEC No.308 connected to cathode.

◆ Greater than 1 megohm.

14F7

High-Mu Twin Triode

The 14F7 is the same as the 7F7 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC) 12.6▲ volts

Current at 12.6 volts. 0.15● amp

14F8

Medium-Mu Twin Triode

The 14F8 is the same as the 7F8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC) 12.6▲ volts

Current at 12.6 volts. 0.15● amp

▲ Nominal voltage = 14 volts.
● Nominal current = 0.16 ampere.

RADIO CORPORATION OF AMERICA
Electron Tube Division

