

7AU7

Medium-Mu Twin Triode

The 7AU7 is the same as the 12AU7A except for the following items:

Heater Characteristics and Ratings

| Heater-section arrangement | Parallel | Series |
|------------------------------|------------------|----------------------|
| Voltage (AC or DC) | 3.5 ^a | 7.0 ± 0.7 V |
| Current | 0.600 ± 0.040 | 0.300 ^b A |
| Warm-up time (Average) . . . | 11 | - s |

^a At 0.600 ampere.

^b At 7.0 volts.

7EY6

Beam Power Tube

The 7EY6 is the same as the 6EY6 except for the following items:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.600 ± 0.040 | A |
| Voltage (AC or DC) at 0.600 A | 7.2 | V |
| Warm-up time (Average) | 11 | s |

7KY6

Sharp-Cutoff-Pentode

The 7KY6 is the same as the 6KY6 except for the following items:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 7.3 | V |
| Warm-up time (Average) | 11 | s |



RADIO CORPORATION OF AMERICA
Electronic Components and Devices

Harrison, N. J.

DATA
4-67