

# 8CS7

---

## Medium-Mu Dual Triode With Dissimilar Units

### CONTROLLED HEATER WARM-UP TIME

The 8CS7 is the same as the 6CS7 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . . .	8.4	volts

# 8CW5

---

## Beam Power Tube

The 8CW5 is the same as the 6CW5 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at 0.600 amp. . . . .	8.0	volts

# 8CX8

---

## Medium-Mu Triode— Sharp-Cutoff Pentode

The 8CX8 is the same as the 6CX8 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at 0.600 amp. . . . .	8.0	volts
Warm-up time (Average) . . . . .	11	sec

# 8EB8

---

## High-Mu Triode—Sharp-Cutoff Pentode

The 8EB8 is the same as the 6EB8 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at 0.600 amp. . . . .	8.0	volts
Warm-up time (Average) . . . . .	11	sec

---

DATA

RADIO CORPORATION OF AMERICA  
Electronic Components and Devices

Harrison, N. J.

