

8CS7

Medium-Mu Dual Triode With Dissimilar Units

CONTROLLED HEATER WARM-UP TIME

The 8CS7 is the same as the 6CS7 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at 0.450 amp. | 8.4 | volts |

8CW5

Beam Power Tube

The 8CW5 is the same as the 6CW5 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.600 ± 0.040 | amp |
| Voltage (AC or DC) at 0.600 amp. | 8.0 | volts |

8CX8

Medium-Mu Triode— Sharp-Cutoff Pentode

The 8CX8 is the same as the 6CX8 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.600 ± 0.040 | amp |
| Voltage (AC or DC) at 0.600 amp. | 8.0 | volts |
| Warm-up time (Average) | 11 | sec |

8EB8

High-Mu Triode—Sharp-Cutoff Pentode

The 8EB8 is the same as the 6EB8 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.600 ± 0.040 | amp |
| Voltage (AC or DC) at 0.600 amp. | 8.0 | volts |
| Warm-up time (Average) | 11 | sec |

DATA

RADIO CORPORATION OF AMERICA
Electronic Components and Devices

Harrison, N. J.

