



- ⚠ USED IN SOME VERSIONS.
 - 7 WHEN INSTALLING NEW 6L6'S RESET O.T. MATCHING FOR MIN. HUM.
 - ⚠ 0.07 MV W/ LEAD "ON"
 - 5. ○ DENOTE TYPICAL 1KHZ SIGNAL REQUIRED FOR 10 WATT OUTPUT AND 700 MV REVERB INPUT COIL DRIVE. (CONTROLS MAX., LEAD OFF)
 - 4. SIX DIGIT NUMBERS ARE FENDER PART NUMBERS.
 - 3. ALL CAPACITORS AT LEAST 600V, W.V.D.C.
 - 2. ALL RESISTORS 1/2 WATT ±10%
 - 1. VOLTAGES READ TO GROUND WITH V.T.M. NO SIGNAL.
- NOTE: UNLESS OTHERWISE SPECIFIED

CAUTION
 500 VOLTS AVAILABLE - DISCONNECT POWER SUPPLY AND ALLOW AT LEAST 20 SECONDS FOR VOLTAGES TO "BLEED" OFF BEFORE SERVICING AMPLIFIER.

Fender / Rogers / Rhodes
 CBS MUSICAL INSTRUMENTS - A DIVISION OF CBS INC.
 FULLERTON, CALIFORNIA 92708

PART NAME
75W LEAD AMP WITH REVERB
 DOMESTIC, EXPORT & JAPAN

RELEASE	REV	PART NO.	REV
	D	017419	
SCALE	MODEL NO.		