


RECTIFIER BULBS AND RENEWALS

The guaranteed average life of the bulb under normal operating conditions is 400 working hours.



30 AMPERES
STYLE NO. 157957



30 AMPERES
STYLE NO. 231580



10 AMPERES
STYLE NO. 222324



5 AMPERES
STYLE NO. 125185



5 AMPERES
STYLE NO. 242127

SPECIFICATIONS AND LIST PRICES

Style No	Description	List Price	ADD FREIGHT		
			Eastern Zone	Central Zone	Western Zone
125185	Bulb for type E outfit, Style No. 152999	\$10 00	\$0 75	\$1 50	\$3 00
125186	Bulb for type E outfit Style No. 154611, 222305 and 7, 220241	11 00	75	1 50	3 00
222324	Bulb for type E outfits Style No. 222306 and 8	11 00	75	1 50	3 00
242127	Bulb for type WI outfit	7 50	20	40	60
222323	Bulb for 15-ampere type W and AT outfit	14 00	75	1 50	3 00
252487	Bulb for 30-ampere type AL outfit	21 00	75	1 50	3 00
231580	Bulb for 30-ampere type W outfit	21 00	75	1 50	3 00
157957	Bulb for 30-ampere type AA, AN, or 20 and 30-ampere type AT outfit	21 00	75	1 50	3 00
114847	Bulb for 50-ampere type AE or 40 and 50-ampere type AT, AL and WL outfit.	37 00	75	1 50	3 00

SPECIAL ORDERING INSTRUCTIONS

Complete information regarding the source of supply and the type and size of battery to be charged, or the nature of the load if not a battery, should be furnished when ordering a rectifier.

60-cycle circuits. Similar outfits can be furnished for other frequencies on application.

Time Switch—The time switch for terminating the charge at a definite hour should always be ordered **when automatic termination of charge is desired.**

Outfits as listed in this catalogue are for use on

Order by Style Number