



12A7

12A7
12A8-GT/G

RECTIFIER-PENTODE

Heater ■	Coated Unipotential Cathodes		
Voltage	12.6	a-c or d-c volts	
Current	0.3	amp.	
Maximum Overall Length		4-17/32"	
Maximum Seated Height		3-29/32"	
Maximum Diameter		1-9/16"	
Bulb		ST-12	
Cap		Small	
Base		Small 7-Pin	
Pin 1-Heater		Pin 5-Rectifier Plate	
Pin 2-Pentode Plate		Pin 6-Pentode Cathode	
Pin 3-Pentode Screen		Pin 7-Heater	
Pin 4-Rectifier Cathode		Cap -Pentode Grid	
Mounting Position	BOTTOM VIEW (7K)		Any
<u>Maximum Ratings Are Absolute Values</u>			
<u>PENTODE UNIT</u>			
Plate Voltage	135 max. volts		
Screen Voltage	135 max. volts		
<u>Typical Operation and Characteristics-Class A₁ Amplifier:</u>			
Plate	135	volts	
Screen	135	volts	
Grid	-13.5	volts	
Cathode Res.	1175	ohms	
Plate Res.	102000	ohms	
Transcond.	975	μmhos	
Plate Cur.	9	ma.	
Screen Cur.	2.5	ma.	
Load Res.	13500	ohms	
Power Output	0.55	watt	
<u>RECTIFIER UNIT</u>			
With Condenser-Input Filter:			
A-C Plate Voltage (RMS)	125 max. volts		
D-C Output Current	30 max. ma.		

12A8-GT/G
PENTAGRID CONVERTER

Heater ■	Coated Unipotential Cathode		
Voltage	12.6	a-c or d-c volts	
Current	0.15	amp.	
The 12A8-GT/G is the same as the 6A8-GT except for heater rating.			

In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.

AUG. 2, 1943

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA