

# 2ER5

## High-Mu Triode

*The 2ER5 is the same as the 6ER5 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A. . . . .	2.3	V

# 2FH5

## High-Mu Triode

*The 2FH5 is the same as the 6FH5 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A. . . . .	2.35	V
Warm-up time (Average) . . . . .	11	s

# 2FS5

## Beam Hexode

*The 2FS5 is the same as the 6FS5 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A. . . . .	2.4	V
Warm-up time (Average) . . . . .	11	s

# 2GK5

## High-Mu Triode

*The 2GK5 is the same as the 6GK5 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A. . . . .	2.3	V
Warm-up time (Average) . . . . .	11	s

