



HEATHKIT STEREO AMPLIFIER MODEL A-100

ENCLOSED NUMBER AND LETTERED DESIGNATIONS APPEAR ON CIRCUIT BOARDS. NUMBERS 20, 21, 22, 25, 43, AND 44 ARE GROUND CONNECTIONS AND DO NOT APPEAR ON THE SCHEMATIC.

ALL PAPER CAPACITORS RATED AT 400 VOLTS DC UNLESS SPECIFIED OTHERWISE.

ALL CAPACITOR VALUES ARE IN μ F UNLESS SPECIFIED OTHERWISE.

ALL RESISTORS ARE 1/2 WATT UNLESS SPECIFIED OTHERWISE.

ROTARY SWITCH WAFERS ARE VIEWED FROM FRONT. SWITCHES SHOWN IN MAX. COUNTERCLOCKWISE POSITION.

→ INDICATES CLOCKWISE ROTATION.

○ INDICATES VOLTAGE READING.

VOLTAGES TAKEN WITH HEATHKIT VTVM. 117 VOLT LINE SOURCE. VOLTAGES MAY VARY $\pm 20\%$ DUE TO TOLERANCE OF COMPONENTS. VOLTAGES MARKED * SHOULD NOT VARY MORE THAN $\pm 10\%$.

DC VOLTAGES TAKEN FROM TEST POINT TO CHASSIS GROUND, UNDER NO-SIGNAL CONDITIONS.